



### MPP-611

High performance grade of micronized polyethylene wax for inks and coatings

#### Features and Benefits

- Imparts excellent rub and mar resistance with good surface slip
- Provides excellent antiblocking properties
- Good heat resistance
- Better resistance to solvent absorption and swelling when compared to Synthetic wax

#### Composition

High density polyethylene

#### Recommended Addition Levels

1.0-3.0% (on total formula weight)

#### Systems and Applications

Water based, solvent based and energy curable coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); powder coatings; interior and exterior can and container coatings; coil coatings; seed coatings.

#### Typical Properties\*

	<u>MPP-611</u>	<u>MPP-611XF</u>
<b>Melting Point ° C</b>	110 - 116	110 - 116
<b>Density @ 25 ° C (g/cc)</b>	0.96	0.96
<b>NPIRI Grind</b>	2.0 - 3.0	1.0 - 2.0
<b>Maximum Particle Size (µm)</b>	22.00	22.00
<b>Mean Particle Size (µm)</b>	5.0 - 8.0	4.0 - 6.0

This product is also available as a water based wax dispersion - Microspersion 611XF-50

Apr-25