

## Microspersion<sup>®</sup> 6515AL-30

A nonionic water based dispersion of a highly engineered HDPE/amide wax/aluminum oxide nanocomposite for maximum scratch, scuff and block resistance

### Features and Benefits

- Convenient, ready-to-use, pourable nonionic wax dispersion
- Maximum scratch resistance; equal to PE/PTFE additives
- HDPE/amide wax composite reinforced with 300 nm aluminum oxide nanoparticles (Mohs Hardness 9)
- Good abrasion resistance with slip and lubricity
- Amide wax component provides excellent antiblocking and release properties
- Ideal for can and container coatings; 21CFR 175.300 approved

### Dry Wax ID

Superslip 6515AL

### Recommended Addition Levels

2.0-5.0% (on total formula weight)

### Systems and Applications

Water based coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); can, container, and coil coatings.

## Typical Properties\*

### Microspersion 6515AL-30

<b>Wax Solids</b>	30%
<b>Viscosity @ 25 ° C (cP)</b>	1,000 - 5,000
<b>pH</b>	8.0 - 9.5
<b>Density @ 25 ° C (g/cc)</b>	0.98
<b>Wax Mean Particle Size (µm)</b>	3.5 - 5.5

Feb-25