

Polyfluo® 150

A unique, high performance composite of polyethylene and PTFE for surface lubricity with scratch and abrasion resistance

Features and Benefits

- High performance product for adding slip, scratch and abrasion resistance
- Synergistic wax combination that enhances PTFE mobility to the coating surface
- High slip polyethylene provides excellent surface lubricity
- PTFE dramatically enhances abrasion resistance
- Extra fine particle size provides excellent gloss retention and film clarity
- Conforms to (EU) 2019/1021 & Stockholm Convention (POP)

Composition

Polyethylene/PTFE

Recommended Addition Levels

0.5-3.0% (on total formula weight)

Systems and Applications

Water based, solvent based and energy curable coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); powder coatings; interior and exterior can and container coatings; rubber additives.

Typical Properties*

	<u>Polyfluo 150</u>	<u>Polyfluo 150XF</u>
Melting Point ° C	113 - 116	113 - 116
Density @ 25 ° C (g/cc)	1.04	1.04
NPIRI Grind	1.0 - 2.0	1.0 - 2.0
Maximum Particle Size (µm)	15.56	11.00
Mean Particle Size (µm)	3.5 - 5.5	3.0 - 5.0

PTFE (PFAS) free alternatives: MPP-611XF, MPP-611AL

Apr-25