

## Polyfluo<sup>®</sup> 535

An economical wax/PTFE combination for surface lubricity with scratch and abrasion resistance

### Features and Benefits

- High performance product for adding slip, scratch and abrasion resistance
- Synergistic wax combination that enhances PTFE mobility to the coating surface
- PTFE dramatically enhances abrasion resistance
- Wax component provides improved surface slip
- Easy to disperse fine powder that can be incorporated with high speed mixing
- Conforms to (EU) 2019/1021 & Stockholm Convention (POP)

### Composition

Wax modified PTFE

### Recommended Addition Levels

0.5-3.0% (on total formula weight)

### Systems and Applications

Water based, solvent based, Industrial coatings (including plastic and metal); wood coatings; printing inks and OPV's (including flexo and gravure); rubber additives;

### Typical Properties\*

	<u>Polyfluo 535</u>
<b>Melting Point ° C</b>	108 - 115
<b>Density @ 25 ° C (g/cc)</b>	1.04
<b>NPIRI Grind</b>	1.0 - 2.0
<b>Maximum Particle Size (µm)</b>	22.00
<b>Mean Particle Size (µm)</b>	5.0 - 6.0

**PTFE (PFAS) free alternatives: MP-28AL, Superslip 6515**

Apr-25