

## PropylTex® 10-50 (coarse texture grades)

Extra coarse particle size grades of micronized polypropylene for adding texture, structure and anti-slip properties to a wide variety of paints and coatings

### Features and Benefits

- Provides a consistent coarse textured coating surface
- Tough, high molecular weight polypropylene gives good film durability
- Does not lower COF; ideal for anti-skid surfaces
- Easy to disperse powder that can be incorporated with high speed mixing

### Composition

Polypropylene

### Recommended Addition Levels

3.0-10.0% (on total formula weight)

### Systems and Applications

Water based, solvent based, industrial and consumer paints including masonry, stucco paints, architectural wall and trim paints; stains, sealers and varnishes; wood coatings; floor coatings.

### Typical Properties\*

	<u>PropylTex 10</u>	<u>PropylTex 14</u>	<u>PropylTex 20</u>	<u>PropylTex 30</u>
<b>Melting Point ° C</b>	166 - 168	166 - 168	166 - 168	166 - 168
<b>Density @ 25 ° C (g/cc)</b>	0.90	0.90	0.90	0.90
<b>Maximum Particle Size (µm)</b>	2000 (10 mesh)	1410 (14 mesh)	841 (20 mesh)	595 (30 mesh)

PROPYLTEX 10 & 14 ARE MADE TO ORDER PRODUCTS WITH MINIMUM ORDER QUANTITIES AND EXTENDED LEAD TIMES

Apr-25