



## PropylTex® 10

Coarsest particle size grade of micronized polypropylene for adding texture, structure and non-slip properties to a wide variety of paints and coatings

### Features and Benefits

- Provides a consistent coarse textured coating surface
- Tough, high molecular weight polypropylene gives good film durability
- Does not lower COF; ideal for non-skid surfaces
- Easy to disperse powder that can be incorporated with high speed mixing

### Composition

Polypropylene

### Recommended Addition Levels

3.0-10.0% (on total formula weight)

### Systems and Applications

Water based, solvent based, industrial and consumer paints including masonry, stucco paints, architectural wall and trim paints; stains, sealers and varnishes; wood coatings; floor coatings.

### Typical Properties\*

**PropylTex 10**

<b>Melting Point °C</b>	166 - 168
<b>Density @ 25 °C (g/cc)</b>	0.90
<b>Maximum Particle Size (µm)</b>	2000 (10 mesh)

THIS IS A MADE TO ORDER PRODUCT WITH MINIMUM ORDER QUANTITIES AND EXTENDED LEAD TIMES

Nov-17

### Micro Powders, Inc.

580 White Plains Road, Tarrytown, NY 10591  
TEL 914.793.4058 FAX 914.472.7098  
Email: mpi@micropowders.com

\*The above data reflects typical properties. Please contact Micro Powders for official product specifications. The information contained herein is to the best of our knowledge true and correct and any suggestions are made without guarantee, express or implied, since conditions of use are beyond our control. Micro Powders, Inc. disclaims any liability incurred in connection with the use of any data or suggestions. Nothing contained herein shall be construed as a recommendation to infringe on any existing patents covering any material or its use.