



### SuperGlide 904

A unique combination of amide wax and synthetic wax that provides slip, scratch and block resistance with a very smooth surface feel

#### Features and Benefits

- EBS provides maximum surface lubricity and block resistance without the use of PTFE
- Provides scratch and mar resistance
- Imparts a smooth surface "feel"
- Provides uniform gloss control at higher dosage levels

#### Composition

Synthetic wax/Ethylene bis(stearamide)

#### Renewable Carbon Index

>70%

#### Recommended Addition Levels

0.5-3.0% (on total formula weight)

#### Systems and Applications

Solvent based and energy curable coatings and inks.  
Industrial coatings (including plastic, metal and leather);  
wood coatings; powder coatings; interior and exterior can  
and container coatings; soft touch coatings.

#### Typical Properties\*

	<u>SuperGlide 904</u>	<u>SuperGlide 904XF</u>
<b>Melting Point ° C</b>	138 - 145	138 - 145
<b>Density @ 25 ° C (g/cc)</b>	0.96	0.96
<b>NPIRI Grind</b>	2.0 - 4.0	1.0 - 2.0
<b>Maximum Particle Size (µm)</b>	22.00	15.56
<b>Mean Particle Size (µm)</b>	4.0 - 6.0	3.0 - 5.0

SUPERGLIDE 904XF IS A MADE TO ORDER PRODUCT WITH MINIMUM ORDER QUANTITIES AND EXTENDED LEAD TIMES

Apr-25